

1972 Formula Ford, redesigned suspension geometry, fabricated front uprights, lighter chassis, complete car now under legal minimum. Complete with Hewland gearbox, championship winning BRM tuned, uprated Ford engine. Complete Palliser dry sump system, mechanical tachometer drive. Dunlop racing tires. SCCA approved roll bar, Varley battery, etc.

Price F.O.B. Port of Entry	· selve	\$ 5,935.00
With standard engine but otherwise as above	• • •	5,599.00
Less engine, but otherwise as above		4,933.00
Less engine and gearbox		4,134.00
Less engine, gearbox and tires		3,934.00
Options: Rubber bag type fuel cell 6 point aircraft harness		163.00 extra 102.00 extra

Ride Height $3\frac{1}{4}$ " with 21" wheels $3\frac{1}{2}$ " with 22" wheels Camber $0^{\circ}-1/8^{\circ}$ neg. $0^{\circ}-1/8^{\circ}$ neg. Castor $5\frac{1}{2}-6^{\circ}$ $0^{\circ}$ Toe in 30 min. 20 min.	Suspension Settings:	Front	Rear
Castor $5\frac{1}{2}-6^{\circ}$ 0°	Ride Height	$3\frac{1}{4}$ " with 21" wheels	$3\frac{1}{2}$ " with 22" wheels
	Camber	00-1/8° neg.	0°-1/8° neg.
Toe in 30 min. 20 min.	Castor	5½-6°	0°
	Toe in	30 min.	20 min.
Swaybar 3" showing 1" showing	Swaybar	3" showing	l" showing

91 - 91<del>2</del>" Wheelbase:


It is important that the donuts be set under tension with about 3/16" pull from static position.

## Winkelmann

## PD-4 Formula Ford

- steel front uprights, magnesium rear upmechanism. the already robust tubular chassis now allowrights and further development has improved redesigned suspension geometry, fabricated The new Formula Ford for 1972 features ing more elbow room for the revised shift
- are fully dry sumped. power. All cars are equipped with the uprated vastly superior handling and cornering this years car has already demonstrated With the reduction of unsprung weight, Cortina GT (Pinto) engine, and the engines
- pinion and metalastic drive couplings. with a changeable first gear, 9-31 ring and Hewland gearboxes are used as standard,
- the various types of crack checking. tractive electroplating process that permits the suspension is now finished with an at-Following current Formula One practice,
- nated, and layed up by hand for lighter Fibreglas body panels are color impreg-
- the kits are: tires, battery, seat belts and to London docks or airport. Excluded from plete kit packaged and crated and delivered The Winkelmann PD-4 is offered as a com-

\*At the rate of £1=\$2.60 Price, fob London docks or airport....£1700\* Less: engine and gearbox .....£1250 \$4420.



## KIT CONTENTS

Oven baked enamel painted chassis... Complete engine and gearbox assemblies — uprated engine, changeable first gearbox.

magnafluxed or dye penetrant crack checked). Totally adjustable zinc irridite electroplated suspension components (can be

Steel fabricated front uprights (3 lb. savings over Triumph type)

Cast magnesium rear uprights, metalastic joints on drive shafts.

4 - 51/2" width steel wheels with Pinto, Capri, Cortina bolt pattern.

Girling brake calipers with racing compound pads.

Four piece hand layed fibreglas color impregnated body with Dzus fittings for ease of removal Adjustable pedal assembly (drivers 5'4" - 6'4" can be accommodated)

Four into one, latest design exhaust system. Molded Fibreglas seat.

High efficiency radiator and oil cooler.

Armstrong 7 step adjustable shocks with springs.

and Aeroquip brake lines as standard equipment. In a separate package shipped from Sausalito will be a complete package of AN fasteners

